



Part Number	Qty for Step	Description
1	2	38" h Vertical extrusion
2	1	38" h Vertical extrusion w/ door hardware
3	1	38" h Vertical extrusion w/ door hardware
4	4	48" h Vertical extrusion
4a	8	Horizontal Counter Supports
5	4	16" Horizontal extrusion
6	4	12.4563" Curved Horizontal extrusion
7	2	19.573" Horizontal extrusion
8	6	20" Curved Horizontal extrusion
9/9A	2/1	20" Horizontal extrusion / 20" Horizontal extrusion w/counter connection




Steps

- 1) Connect lower horizontal extrusions [5 - 9] between vertical extrusions [1 - 4] as shown below.
- 2) Place inserts and door as indicated connecting upper horizontal extrusions [5 - 9A] as shown.
- 3) Attach shelf supports to velcro located inside pedestal, place internal shelf atop shelf supports.
- 4) Place counters atop assembled pedestal.


Slide Door into Place atop Hinge as shown.



Before placing small counter atop Pedestal connect extrusions [4a] flush to top of 48" h vertical extrusions [4] for support.



* = Indicates pin location for counter placement



WHEN DISASSEMBLING ALUMINUM EXTRUSION, TIGHTEN ALL SETSCREWS AND LOCKS TO PREVENT LOSS DURING SHIPPING

visionary™ IDESIGNS

Using Your Setup Instructions

The Visionary Designs Setup Instructions are created specifically for your configuration. They are laid out sequentially, including an exploded view of the entire display, and then a logical series of detailed steps to assemble the main structure and components. We encourage you to study the instructions **before** attempting to assemble your exhibit.

Each page reminds you to tighten the setscrews after disassembling your exhibit to prevent loss of the locks and setscrews (see below in RED). This is **VERY IMPORTANT**.

Cleaning and Packing Your Display

- 1) Use care when cleaning aluminum extrusion or acrylic inserts. Use only non-abrasive cleaners.
- 2) When cleaning laminate inserts or countertops, use mild cleansers and a soft material such as cotton.
- 3) Keep all display components away from extreme heat and long exposure to sunlight to avoid warping and fading.
- 4) Retain all packing material. It will make re-packing much easier and will reduce the likelihood of shipping damage.



The Tool

Most Visionary Designs exhibits can be assembled with the supplied Hex Key Tool. Occasionally, a flat head screwdriver may be required.




Detail A

Typical Connection



Typical Connection (cont'd)

Most horizontal extrusion connections have a patented expandable lock. This lock inserts into the groove of an opposing extrusion. Tightening the lock with the Hex Key Tool expands the lock and creates a strong positive connection.



Detail B

Numbered Label


Each extrusion contains a numbered label which corresponds with setup instructions. The label is located within a groove of the extrusion (when possible). With Visionary Designs the labels contain Black numbers unless otherwise specified.



Detail C

Horizontal Inline Connection (remove only one setscrew)


Remove only (1) setscrew when disassembling. Replace setscrew in extrusion after assembling it. Before packing, replace setscrew in extrusion to avoid losing it.



Detail D

Base Plate Connection

Attach base plate to round or square vertical extrusion using the bolt provided. Be careful not to strip the threads.



Detail E

Vertical Connection
(remove only two setscrews)

When vertical extrusions are packed in portable cases rather than crates or tubs, they must be broken down into smaller sections which then require assembly.

Remove only (2) setscrews when disassembling. Replace setscrews in extrusion after assembling it. Before packing, replace setscrews in extrusion to avoid losing them.

WHEN DISASSEMBLING ALUMINUM EXTRUSION, TIGHTEN ALL SETSCREWS AND LOCKS TO PREVENT LOSS DURING SHIPPING